



**Futtertype:
Röhm KFA 200/2**



Weiche Aufsatzbacke mit Spitzverzahnung 1/16°90° Nut=21mm					Nutenstein: GE25		
B	H	L	kg/Satz	Typ	Ident-Nr.	Werkstoff	
70	70	95	7,2	DS20	207003	C15	




Ausführung: Rohlinge, ungebohrt				Nutenstein: GE25			
45	60	90	6,8	RB10	200052	16MnCr5	
50	50	90	5,1	RB15	200053	16MnCr5	
50	80	90	8,3	RB25	200055	16MnCr5	
60	60	90	7,3	RB35	200057	16MnCr5	
60	60	105	8,5	RB40	200058	16MnCr5	
60	80	90	9,9	RB45	200059	16MnCr5	
60	80	105	11,6	RB50	200060	16MnCr5	
60	80	120	13,2	RB55	200061	16MnCr5	
64	102	120	16,8	RB60	200062	C15	
64	127	120	20,4	RB65	200063	C15	
80	60	120	13,2	RB70	200064	16MnCr5	




Gehärtete Greiferspannbacken, Außenspannung

auf Anfrage




Gehärtete Greiferspannbacken, Innenspannung

auf Anfrage



Gehärtete umkehrbare Aufsatzbackenbacken

auf Anfrage




Nutensteine

H	h	N	G	Typ	Ident-Nr.	Werkstoff	
25,5	11	21	M16	GE25	291003	40NiCrMo6	

Auflagebolzen

auf Anfrage




Gripper Hartmetall



Ausdrehvorrichtung



Stangengreifer



Reinigungsplatte



Pendelbacken

Stand: 10/2003